
SPIGOT CONNECTOR COUPLINGS

WATGZ 4" - 6" Pipe



WATGZ 8"-16" Pipe



WATGZ 16" - 104" Pipe



Stainless Steel Spigot Connectors for Sewer pipe, come with EPDM, NBR/Nitrile or Silicone elastomer and stainless steel compression tighteners.

The outer thickeners insures the tightness of the connection, the wider band tighteners secure the pipe ends.

WAT Spigot connectors fit PVC, Concrete, Cast iron and HDPE Pipes.

Please provide the following information when ordering:

The outer diameter of pipes to be connected.
The material required for the seal (EPDM, NBR, Silicone).

Spigot Connector Couplings

Pipe Of Different Diameters Connectors and Direct-In Multi Pipe Connectors

WATGZ Different Diameter



WATGZ Direct-IN



Please provide the following information when ordering:

The outer diameter of each pipe to be connected.
The material required for the seal (EPDM, NBR, Silicone).

For Direct-In connections we require the ID of the end Pipe and OD of Direct-In Pipes

WATGZ 4" - 6" Pipe



The range of diameters [mm]	Connector length [mm]
100 - 110	100
111 - 125	120
126 - 145	120
146 - 165	150
166 - 185	150

WATGZ 8"-16" Pipe



Symbol	The range of diameters [mm]	Connector length [mm]
GZ 200	186 - 200	150
GZ 220	201 - 220	180
GZ 240	221 - 235	180
GZ 250	236 - 245	180
GZ 260	246 - 265	180
GZ 280	266 - 290	200
GZ 310	291 - 315	200
GZ 330	316 - 340	200
GZ 360	341 - 365	200
GZ 380	366 - 395	200

WATGZ 16" - 104" Pipe



Symbol	Diameter range	The length of the connector
GZ - 450	396 - 480	250
GZ - 500	481 - 720	250
GZ - 750	721 - 960	250
GZ - 1000	961 - 1200	250
GZ - 1250	1201 - 1440	250
GZ - 1500	1441 - 1680	250
GZ - 1750	1681 - 1920	250
GZ - 2000	1921 - 2160	250
GZ - 2250	2161 - 2400	250
GZ - 2500	2401 - 2640	250